

P-DP Tape Printer

ISO 9001:2000
Registered

Mini-Tape Printer

High quality impact printer to replace bulky, expensive printers in applications where portability is a must.

This small and versatile printer is excellent for printing out weight results, is available in RS232C and 20mA interfaces, and is the perfect companion to your Intercomp CW500 Floor Scale, PT300 Wheel Load Scale or LP600 Low-Profile Wheel Load Scale Systems.

This printer uses plain, inexpensive, easy to find adding machine paper that does not gum up the print head. Printouts are sharp and never fade.

The ribbon cartridge is easily replaced and is available in black or purple.



Printable Characters

Interface:

RS232C - 9 Volts to 9 Volts

Line Buffering:

Full column buffering for line at a time printing and automatic text wrapping.

Print Method:

Impact Dot Matrix

Character Matrix:

5x8 Dot Matrix

Character Spacing:

24 Column

12.8 Characters/inch

Line Feed Spacing:

7.6 Lines/in - Character Mode

9.1 Lines/in - Graphic Mode

Print Speed:

38 Lines per Minute (24 Column)

Paper:

2.25x2.75"(57x70 mm)/0.44" (11 mm) ID

Power:

1 Watt Idle, 10 Watts while Printing

AC Voltage:

9 VAC - 120 VAC Converter Included

220 Volt Optional

DC Voltage:

9 - 12 VDC Optional

100mA idle, 1500mA while Printing

2.9A Peak

External Dimensions:

4.1x4.5x2" (104x114x50mm)

Operating Temperature:

41° to 104° F (5° to 40° C)

Print Head Life:

500,000 Character Lines

Ribbon Life:

Black: 20,000 Characters

Purple: 250,000 Characters

Paper:

Small Roll: 3,000 Lines

Large Roll: 12,500 Lines

sales@intercompcompany.com

Toll Free: 800-328-3336

Worldwide: 763/476-2531

Fax: 763/476-2613

Intercomp
advanced weighing technology... by any measure

3839 County Road 116
Medina, Minnesota 55340-9342 U.S.A.

All Rights Reserved

intercompcompany.com