

Thermal Printer

ISO 9001:2000
Registered

Mobile Thermal Printer

Interface:

IrDA
Bluetooth
Serial

Print System:

Direct Thermal Printing

Character Matrix:

ASCII Code
Alphanumeric Characters
International Characters
Windows Code Page

Characters Per Line:

Font A: 32 Characters per Line
Font B: 42 Characters per Line

Print Speed:

50mm per Second

Paper:

58mm Wide

Power:

2 Watts Idle, 15 Watts while Printing

AC Adapter:

Input Voltage: 90V - 264 V AC
Output Voltage: 9.0V - DC 1.0 A

Battery:

Li-ion Battery Pack

Battery Life:

30,000 Lines

External Dimensions:

4.5x4x2.5" (116x104x63mm)

Weight:

1 lb (370 g)

Operating Temperature:

41° to 104° F (5° to 40° C)

High quality, compact, fully-featured thermal printer can be used in a variety of environments.

This small and versatile printer is excellent for printing out weight results, is available in IrDA, Bluetooth and Serial interfaces, and is the perfect companion to your Intercomp CS Series Crane Scale, TL6000 Tension Link Scale, CW250 Platform Scale, Twin Beam or U-Beam Scale, Wheel Load Scale and Mining Scale Systems as well as a great accessory for your Intercomp GP Series Indicator.

```
INTERCOMP, U.S.A.  
TEL: 763-476-2531  
  
***VEH #1***  
SCALE 1: 4,998 lbs  
SCALE 2: 4,957 lbs  
SCALE 3: 4,963 lbs  
SCALE 4: 4,985 lbs  
.:  
.:  
  
TOTAL WEIGHT: 19,903lbs
```

Printable Characters



sales@intercompcompany.com

Toll Free: 800-328-3336

Worldwide: 763/476-2531

Fax: 763/476-2613

Intercomp[®]
advanced weighing technology... by any measure

3839 County Road 116
Medina, Minnesota 55340-9342 U.S.A.

All Rights Reserved

intercompcompany.com